

PRODUCT DESCRIPTION

An environmentally friendly, easy to apply, good quality Matt Acrylic emulsion for use as an interior/exterior finishing coat or interior primer. It has been formulated with an optimum blend of acrylic resins, precisely graded fillers and fade resistant pigments. It offers excellent hiding power and has good grain filling properties. The product conforms to GBCSA environmental requirements and EU 2010 targets.

COLOUR RANGE

White, Pastel and Medium colours.

Refer to the Midas 300 colour range. Colours are tinted at the point of sale.

SPECIAL NOTE: Colours can be tinted using Zero VOC, Glycol Free, APEO free, NPEO free, and Formaldehyde free strainers which do not add to the VOC of the product, unlike the standard tinters used within the paint industry.

PACKAGING

1 litre, 5 litre and 20 litre

RECOMMENDED FOR

INTERIOR and EXTERIOR surfaces.

Used as interior primer for new or previously painted sand/cement plaster, concrete, fairfaced brickwork, gypsum boards (suitably primed when new) and building boards. Also used as an economical finishing coat for interiors and ceilings, as well as asbestos and fibre cement.

NOTE: Refer to the occupational health & safety act 1993 (ACT NO.85 of 1993) ASBESTOS REGULATIONS, 2001; for working with asbestos fibre products.

NOT RECOMMENDED FOR

Not suitable for areas of high traffic or humidity.

APPLICATION

PLEASE NOTE: Correct preparation is essential. All surfaces must be sound and prepared in the recommended manner.

For more information on surface preparation contact your closest Paintsmiths store.

After the correct surface preparation has been completed apply the necessary primer coat.

Then thoroughly stir and apply a minimum of 2 coats Midamax 190 to prepared surfaces using a brush, roller or spray at the stipulated spread rates.

Allow to dry before over-coating.

SPREAD RATE

± 8m²/litre/coat

NOTE: The spread rates quoted are approximate and should only be used as a guide as the actual rate will vary depending on the condition and porosity of the substrate.

OVERCOATING TIME

> 6 hours

NOTE: It is very important that over coating times, as set out for the various products, are adhered to and also that the prevailing weather conditions are taken into account. Ambient and substrate temperatures, humidity and wind etc. can influence drying times of all coatings. Performance problems can occur if any of the previous coats have not been allowed to dry properly before being overcoated.

IMPORTANT: To prevent surface contamination, coatings must not be left longer than 48 hours between coats. If environmental or weather conditions have caused surface contamination, all surfaces must be thoroughly washed down before applying the next coating.

CLEANERS/SOLVENTS

Water

PREVENTING PROBLEMS AND GENERAL INFORMATION

IMPORTANT: Walls (cement plaster, concrete or masonry) must be dry before painting and should not exceed a moisture content of 10% as measured with a Protimeter Surveymaster Moisture Meter or equal. The ambient temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.

- Excessive application thickness and/or rapid drying could lead to mud cracking.
- Always keep a wet edge and avoid downing tools during the application process to prevent lap marks and variances in colour or texture. Work from corner to corner, or from a natural cut off point to another. Do not attempt touch ups, but redo complete panels.
- Whilst medium quality products may be suitable for exterior use, higher quality products will offer superior performance.

ENVIRONMENTAL NOTE

Please note: Disposal of paint containers and/or contents other than in an approved manner may result in contamination of our water ways or the pollution of our environment. Do not clean equipment where water and solvents will enter storm water drains. Please dispose of unused paint and paint containers through an approved recycling scheme or seek advice from our local council about other accepted disposal methods. For more information on our environmental policies, enquire in store.

VOC GREEN FILTER

The information herein provided is based upon our current theoretical compositions/calculations, and current data from our raw material suppliers.

We thus reserve the right to amend and correct when/if necessary.

FOOTNOTE

The above information is intended as a guide only. Since this product is applied by 3rd parties, Paintsmiths and Kansai Plascon cannot be held liable for any loss or damage whatsoever relating to application or to the surface to which it is applied. Paintsmiths and Kansai Plascon reserves the right to make changes at any time, without notice.



TECHNICAL DATA

Viscosity	120 - 125ku
Specific Gravity	1.55 g/ml +/- 0,05
pH	9 - 9.5
Weight Solids Content	62% (+/- 5%)
Fineness of grind	< 60 microns
Volume Solids Content	41% (+/- 5%)
Pigment Volume Concentration	77% (+/- 5%)
Spread Rate	8 m ² /litre/coat
Dry Film Thickness	51 microns
Surface Dry	< 1hrs
Hard Dry	< 4hrs
Overcoat	> 6hrs
Sheen 20° (on glass @ 100 microns	matt
Sheen 60° wet film thickness	matt
Sheen 85° after 24hrs)	matt
Diluant/Cleaning	water
Application Temperatures	> 10° < 35°
Storage Temperatures	> 5° < 35°
Shelf Life in unopened containers	12 months
VOC level	Zero VOC <1 g/litre*
Drying Mechanism	water evaporation followed by coalescence
Scrubs	N/A
Vehicle Type	Styrene Acrylic
Pigment Type	Rutile Titanium
Application	brush, roller or spray

All tests are performed at 23°C and 50% relative humidity.
Contact our Technical Department on 021 551 5570 should you require any further information.
Material Safety Datasheets are available on request.

* This VOC value is determined using Glycol-free stainers.



ENVIRONMENTAL NOTE

Please note: Disposal of paint containers and/or contents other than in an approved manner may result in contamination of our water ways or the pollution of our environment. Do not clean equipment where water and solvents will enter storm water drains. Please dispose of unused paint and paint containers through an approved recycling scheme or seek advice from our local council about other accepted disposal methods. For more information on our environmental policies, enquire in store.

VOC GREEN FILTER

The information herein provided is based upon our current theoretical compositions/calculations, and current data from our raw material suppliers.

We thus reserve the right to amend and correct when/if necessary.

FOOTNOTE

The above information is intended as a guide only. Since this product is applied by 3rd parties, Paintsmiths and Kansai Plascon cannot be held liable for any loss or damage whatsoever relating to application or to the surface to which it is applied. Paintsmiths and Kansai Plascon reserves the right to make changes at any time, without notice.