

PRODUCT DESCRIPTION

A solvent-based wax used to enhance various Earthcote finishes.
When applied and polished it accentuates and lifts the finish it is being applied to.

COLOUR RANGE

Clear Wax.

PACKAGING

500ml and 2 litre tin

RECOMMENDED FOR

INTERIOR surfaces.
Used as a finishing coat over Earthcote Worn Leather Paint and Earthcote Pandomo.

NOT RECOMMENDED FOR

Not suitable for exterior use, or as a sealer. Do not apply near sources of heat e.g. fireplaces, as it can become soft and dirt retentive when exposed to heat.

APPLICATION

PLEASE NOTE: For more information on surface preparation contact your nearest Paintsmiths store.

Apply the first coat of Earthcote Wall Wax to chosen surface with a lint-free mutton cloth. Spread out thinly and evenly and allow to dry for at least 30 minutes before polishing the entire waxed area by hand or by Orbital buffing machine. Apply a second coat of Earthcote Wall Wax in the same manner.

The more coats of Earthcote Wall Wax applied, the more lustrous and richer the coating will become.

IMPORTANT: Earthcote Pandomo must be sanded with 320 grit water paper before waxing. Earthcote Worn Leather Paint does not require sanding before applying Earthcote Wall Wax.

SPREAD RATE

+/- 40m² per 2 litre tin

NOTE: The spread rates quoted are approximate and should only be used as a guide as the actual rate will vary depending on the condition and porosity of the substrate.

OVERCOATING TIMES

30 minutes

NOTE: It is very important that overcoating times, as set out for the various products, are adhered to and also that the prevailing weather conditions are taken into account. Ambient and substrate temperatures, humidity and wind etc., can influence drying times of all coatings. Performance problems can occur if any of the previous coats have not been allowed to dry properly before being overcoated.

IMPORTANT: To prevent surface contamination, coatings must not be left longer than 48 hours between coats. If environmental or weather conditions have caused surface contamination, all surfaces must be thoroughly washed down before applying the next coating.

CLEANERS/SOLVENTS

Mineral Turpentine

PREVENTING PROBLEMS AND GENERAL INFORMATION

- Earthcote Wall Wax is purely a decorative finish and offers limited sealing properties.
- For splash backs or wet areas, and surfaces behind hobs or stoves, apply one or two coats of Midas Colour Retaining Primer followed by two coats of Earthcote Wall Wax.
- Do not apply too thickly in first application and allow to dry fully before buffing. Premature buffing can cause some of the coating to be removed.
- Avoid downing tools during the application process to prevent lap marks and variances in colour or texture.
- Work from corner to corner, or from a natural cut off point to another.
- Do not attempt touch ups, but redo complete panels.
- Store in dry ambient conditions. Shelf life - 12 months.

ENVIRONMENTAL NOTE

Please note: Disposal of paint containers and/or contents other than in an approved manner may result in contamination of our water ways or the pollution of our environment. Do not clean equipment where water and solvents will enter storm water drains. Please dispose of unused paint and paint containers through an approved recycling scheme or seek advice from our local council about other accepted disposal method. For more information on our environmental policies, enquire in store.

VOC GREEN FILTER

The information herein provided is based upon our current theoretical compositions/calculations, and current data from our raw material suppliers. We thus reserve the right to amend and correct when/if necessary.

FOOTNOTE

The above information is intended as a guide only. Since this product is applied by 3rd parties, Paintsmiths and the manufacturer cannot be held liable for any loss or damage whatsoever relating to application or to the surface to which it is applied. Paintsmiths and the manufacturer reserve the right to make changes at any time, without notice.

TECHNICAL DATA

Viscosity	Paste
Specific Gravity	0.852 g/ml $\pm$ 0,05
pH	N/A
Weight Solids Content	21% $\pm$ 5%
Fineness of grind	N/A
Volume Solids Content	Not determined
Pigment Volume Concentration	Not determined
Spread Rate	40m ² per 2 litre tin
Dry Film Thickness	N/A
Surface Dry	N/A
Hard Dry	N/A
Polishing/Overcoat	> 30 minutes
Sheen 20°	N/A
Sheen 60°	N/A
Sheen 85°	N/A
(on glass @ 100 microns WFT after 24hrs)	
Diluent/Cleaning	Mineral Turpentine
Application Temperatures	> 10° < 35°
Storage Temperatures	> 5° < 35°
Shelf life in unopened containers	12 months
Drying Mechanism	N/A
Scrubs	N/A
Vehicle Type	Wax Emulsion
Pigment Type	N/A
Application	Lint-free mutton cloth

All tests are performed at 23°C and 50% relative humidity.
Contact your nearest store for Technical Advice should you require any further information.
Safety Datasheets are available on request.

ENVIRONMENTAL NOTE

Please note: Disposal of paint containers and/or contents other than in an approved manner may result in contamination of our water ways or the pollution of our environment. Do not clean equipment where water and solvents will enter storm water drains. Please dispose of unused paint and paint containers through an approved recycling scheme or seek advice from our local council about other accepted disposal method. For more information on our environmental policies, enquire in store.

VOC GREEN FILTER

The information herein provided is based upon our current theoretical compositions/calculations, and current data from our raw material suppliers. We thus reserve the right to amend and correct when/if necessary.

FOOTNOTE

The above information is intended as a guide only. Since this product is applied by 3rd parties, Paintsmiths and the manufacturer cannot be held liable for any loss or damage whatsoever relating to application or to the surface to which it is applied. Paintsmiths and the manufacturer reserve the right to make changes at any time, without notice.